



The TDA18250B is a silicon tuner designed specifically for worldwide cable and terrestrial digital Set Top Boxes (STB).

- The TDA18250B ensures a low system cost by saving external components such as:
 - Low-Noise Amplifiers
 - Surface Acoustic Wave (SAW) filters
 - RF splitter

Moreover, thanks to its 8 kV ESD capability, EIA/JESD22-A114 (HBM), on the RF input pin and the loop-through pin, the application level ESD protection can be reduced.

- The TDA18250B silicon tuner meets current and future digital cable and terrestrial TV reception with:
 - Low-power consumption
 - High linearity
 - Very low noise figure (3.6 dB typical)
 - High immunity to wireless interferers (WLAN, LTE and GSM)
- The TDA18250B ensures ease of use with:
 - Easy on-board integration
 - Efficient and effective PCB design
 - Reduced external components

Features and benefits

- Single 3.3 V supply voltage
- RF frequency coverage up to 1 GHz
- Flexible low IF output from 3 MHz to 7.5 MHz to ease the matching with various demodulators
- RoHS compliant
- I²C-bus interface compatible with 3.3 V microcontrollers
- Strong immunity to wireless interferers (WLAN, GSM, LTE)
- Multi-reference clock frequency compliant: 16 MHz, 24 MHz, 25 MHz, 27 MHz, 30 MHz
- Crystal oscillator output buffer to drive demodulator, SoC or slave tuner
- Slave Tuner Output (STO), integrated splitter for dual tuner applications
- Fully integrated oscillators
- LT output
- Fully integrated IF and RF selectivity; eliminating the need for external SAW filters
- Single-ended RF input (no need for external balun)
- Enhanced ESD protection (8 kV) on RF_IN and LT pins
- Alignment free
- Excellent return loss compatible with cable requirements
- Integrated RSSI function, readable through I²C-bus
- Integrated temperature sensor
- Integrated gain control

Applications

- Digital cable STB applications:
 - DVB-C
 - J83.B
 - J83.C
- Digital terrestrial STB applications:
 - DTMB
 - DVB-T/T2
 - ISDB-T
- PVR
- DOCSIS 2.0 cable modem

▮ **Parametric search** all Cable and terrestrial silicon tuners

All information on this product information page is subject to the subsequent disclaimers:

- General product disclaimer

- [General product disclaimer](#)
- [Quality and reliability disclaimer](#)

Parametrics of this product

Type number	Package	Package name	Supply voltage (V)	CSO / CTB [Typ] (dB/dB)	Noise figure [Typ] (dB)	Return loss [Typ] (input dB)	Cable type	Terrestrial type	Total power consumption [Typ](mW)	DVB-T	DVB-T2	DVB-C	DVB-C2	DVB-H	ISDB-T / DTMB	Frequency range (MHz)	Phase noise @ 10KHz [Typ] (dBc/Hz)	RSSI Accuracy Abs. [Typ](dB)	RSSI Accuracy Rel. [Typ](dB)	Number of channels in application	Loop-Through (LT)
TDA18250BHN	SOT617-3 (HVQFN32)	HVQFN32	3,3	-60/-60	4.5	-8	Y	Y	750	Y	Y	Y	Y	Y	Y	42 - 1002	-85	3	0.5	2	Y

Similar products

- [Parametric search](#) all Cable and terrestrial silicon tuners
- [Parametrics series](#)

Package

Type number	Orderable part number	Ordering code (12NC)	Product status	Package	Packing	Marking
TDA18250BHN/C1	TDA18250BHN/C1Y	9352 996 51518	Volume production	SOT617-3 (HVQFN32)	Reel Dry Pack, SMD, 13"	Standard Marking
TDA18250BHN/C1	TDA18250BHN/C1E	9352 996 51551	Volume production	SOT617-3 (HVQFN32)	Tray Dry Pack, Bakeable, Single	Standard Marking
TDA18250BHN/C1	TDA18250BHN/C1K	9352 996 51557	Volume production	SOT617-3 (HVQFN32)	Tray Dry Pack, Bakeable, Multiple	Standard Marking

Outline drawing

Package Version	Package Name	Package Description	Reference Codes	Issue Date
SOT617-3	HVQFN32	plastic thermal enhanced very thin quad flat package; no leads; 32 terminals; body 5 x 5 x 0.85 mm	MO-220 (JEDEC);	2002-10-22

Related documents

Brochure

- [NXP solutions for consumer and computer interfaces \(pdf\) \(2012-04-25\)](#)

Reflow soldering

- [sot617-3_fr \(pdf\) \(2009-10-08\)](#)

Quality, reliability & chemical content

Type number	Orderable part number	Chemical content	RoHS	Leadfree conversion date	RHF	IFR (FIT)	MTBF (hours)	MSL	MSL LF
TDA18250BHN/C1	TDA18250BHN/C1Y	TDA18250BHN/C1	EU/CN RoHS COMPLIANT 	Always Pb-free				3	3
TDA18250BHN/C1	TDA18250BHN/C1E	TDA18250BHN/C1	EU/CN RoHS COMPLIANT 	Always Pb-free				3	3
TDA18250BHN/C1	TDA18250BHN/C1K	TDA18250BHN/C1	EU/CN RoHS COMPLIANT 	Always Pb-free				3	3

[Quality and reliability disclaimer](#)

Ordering & availability

Type number	Ordering code (12NC)	Orderable part number	Region	Distributor	In stock	Order quantity	Inventory date	Buy online	Samples
TDA18250BHN/C1	9352 996 51518	TDA18250BHN/C1Y	ASIA	WPI	35,800	6000	05/14/2013	Buy	not available
TDA18250BHN/C1	9352 996 51551	TDA18250BHN/C1E							
TDA18250BHN/C1	9352 996 51557	TDA18250BHN/C1K	ASIA	WPI	12,250	2450	05/14/2013	Buy	not available

Sample

Sample orders normally take 2-4 days for delivery.

If you do not have a direct account with NXP our network of global and regional distributors is available and equipped to support you with NXP samples. As a NXP customer you also have the option to order samples via our sales organisation.

Technical support

Do you want to ask technical questions to an NXP expert?

Please select one of the following options:

Do you want to ask technical questions to an NXP expert?

Please select one of the following options:

- Use our e-mail form to ask a question
.....
- Find answers in our technical support site.
.....