中文(简体) 日本語



Home

Products Search Support About Us

<u>Home</u> > <u>Search Engine</u> > Catalog: XHTGD19M200F1Q50R0

Timing Device > Crystal Unit

How to check EU RoHS Compliance of Our Products is here.

Product Lifecycle Stage in Production

Recommended Rank Preferred

Specifications

Global Part Number	XHTGD19M200F1Q50R0	
Previous Part Number		
Lead Style	SMD	
Nominal Frequency	19.2000MHz	
Frequency Tolerance	±10ppmmax. (25±3°C)	
Equivalent Series Resistance	80ohm max.	
Temp. Stability	±12ppmmax.	
Operating Temperature Range	-30 to +105℃	
Frequency Aging	±0.7ppmmax./year	
Drive Level	100μW max.	
Load Capacitance	7pF	
Wash	Not Available	
Ultrasonic Wash	Not Available	
Use	For consumer electronics	
Note		

Details

PDF

PDF

English

خ	Part Numbering
ż	Appearance Appearance
خ	Dimensions
ż	Features, Applications
٤	Temperature Characteristics
ž.	Standard Land Patterns
ė.	Notice
٤	Packaging
;	Minimum Quantity

Measument circuit

Minimum Quantity

180mm Paper Tape	
180mm Embossed Tape	3000
330mm Paper Tape	
330mm Embossed Tape	
Bulk Case	
Bulk(Bag)	
Ammo Pack	
320Reel	
Magazine	
Вох	

specifications before ordering.
Please read rating and !Cautions first.
Product specifications in this catalog are as of May 2014
Please make sure to read the Murata's Product Policy, too.

All products and company names herein are trademarks or registered trademarks of their respective owners.

UP.

| Site Map | History | Terms of use | Privacy Policy |

All Rights Reserved, Copyright® Murata Manufacturing Co., Ltd.

Downloaded from Arrow.com. 8/13/2014