



Actual

Catalog Number: HAM0707U
Product ID: 7TCA297090R0115
EAN Number: 05011949016064
Status: Active

Liquid Tight Fitting for Conduit, Universal Gland, Straight with External Male Thread, Conduit Size 40mm, M40 Thread, CSA, Group I & II, Zones 1, 2, 21 and 22, Class I Div1 BCD (Rigid Conduit Only), Class II Div1 EFG, Brass with Epoxy Resin Barrier

North American Specifications (UNSPSC)

UNSPSC	39121420 Liquid tight connectors
IGCC	4585 Liquid tight connectors
Brand Name	Kopex
Type	Liquid Tight Conduit Fitting with Flameproof Barrier
Application	Ideal for Ex I & II 2 GD Gas and Dust, Exde IIC and Exe II Applications
Standard	CSA 060582, ATEX: Sira 09ATEX1231X, IEC EN 60079-0, 60079-1, 60079-7, 60079-31
Size	Conduit Size 40mm
Connection	Straight M40 Thread
Material	Brass with Epoxy Resin Barrier
Color	Metallic
Insulation	IP66 Rating
Temperature Rating	-60 to 130 Degrees C
Environmental Conditions	Hazardous Area Locations

European Specifications (ETIM)

ETIM	EC001180 Screw connection for protective metallic hose
Nominal diameter	40mm
Nominal size in inch	1 1/4 inch
Degree of protection (IP) conduit dependant	IP66-IP66
Model	Straight
Revolving thread	N
Construction type	External thread
Thread type	Metric
Thread connection size	M40 x 1.5
One-piece	Y
Material housing	Brass
Surface protection	Untreated
Approved in combination with protective conduit DIN EN 61386-23	N
Approved in combination with protective conduit CSA	Y
Approved in combination with protective conduit UL	N
Approved in combination with protective conduit FI	N
Operating temperature	-60-+130°C

Packaging

Inner Quantity	1
Outer Quantity	30
Outer Dimensions (inches)	14x14x16
Weight Uom	1.73 lbs. Each

Documents / Support Tools

Technical Drawing / Data Sheet Canada Available on Website

Header

3D Model

Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com