

Save with BMP®41 Label Printer Starter Kits



BMP®41 Starter Kits

Catalog #	Description
BMP41-KIT-VD	BMP41 DataComm Starter Kit
	1 - BMP41 Label Maker Standard Package (BMP41-KIT)
	1 - BMP41 Hard Case (BMP41-HC)
	1 - 1.0" White B-427 Cartridge (M-51-427)
	1 - 0.475" White B-412 Cartridge (MC-475-412)
	1 - 1.0" Black on Yellow B-595 Cartridge (MC1-1000-595-YL-BK)
BMP41-KIT-EL	BMP41 Electrical Starter Kit
	1 - BMP41 Label Maker Standard Package (BMP41-KIT)
	1 - BMP41 Hard Case (BMP41-HC)
	1 - 1.0" White B-427 Cartridge (M-143-427)
	1 - 1.0" White B-498 Cartridge (M-48-498)
	1 - 0.75" White B-342 Cartridge (M-187-075-342)
BMP41-KIT-GI	BMP41 Facility ID Starter Kit
	1 - BMP41 Label Maker Standard Package (BMP41-KIT)
	1 - 1.0" Black on Yellow B-595 Cartridge (MC1-1000-595-YL-BK)
	1 - 1.0" Red on White B-595 Cartridge (MC1-1000-595-WT-RD)
	1 - 1.0" White on Green B-595 Cartridge (MC1-1000-595-GN-WT)
	1 - 1.0" Black on White B-595 Cartridge (MC1-1000-595-WT-BK)

*Printer ships with BMP41 Rechargeable Battery Pack, 29YJ44 cartridge, USB Cable, AC Adapter, Product CD, Brady Printer Drivers CD, Quick Start Guide and 2 Year Warranty.

Indoor / Outdoor Grade Facility & Safety Labels

This low-shrink, continuous vinyl material is pliable with an extremely aggressive adhesive that conforms to smooth or rough surfaces. Ideal for lean 5S labels, pipe markers, equipment and panel labels, and production area ID. Vinyl material has 8-10 years average outdoor durability.* These labels offer excellent resistance to oils, detergents, dirt, grime and many solvents.

- **B-595 Indoor/Outdoor Vinyl Material** - Permanent adhesive, very pliable, good for rough surfaces and outdoor use, wide range of colors. Temp. Range: -40°F to 180°F (-40°C to 82°C). UL recognized.



Figure 33



Fits Printer Models	Diagram	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Roll Length B Inch (mm)	Labels/Roll	Ribbon in Cartridge
B-595 – Indoor/Outdoor Vinyl Tape									
BMP41, 51, 53	Fig. 33	MC-500-595-WT-BK	B-595	Vinyl	BK on WT	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-750-595-WT-BK	B-595	Vinyl	BK on WT	0.750 (19.1)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-WT-BK	B-595	Vinyl	BK on WT	1.000 (25.4)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-YL-BK	B-595	Vinyl	BK on YL	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-750-595-YL-BK	B-595	Vinyl	BK on YL	0.750 (19.1)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-YL-BK	B-595	Vinyl	BK on YL	1.000 (25.4)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-OR-BK	B-595	Vinyl	BK on OR	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-750-595-OR-BK	B-595	Vinyl	BK on OR	0.750 (19.1)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-OR-BK	B-595	Vinyl	BK on OR	1.000 (25.4)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-BL-WT	B-595	Vinyl	WT on BL	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-BL-WT	B-595	Vinyl	WT on BL	0.750 (19.1)	25 ft. (7.6 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-BL-WT	B-595	Vinyl	WT on BL	1.000 (25.4)	25 ft. (7.6 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-RD-WT	B-595	Vinyl	WT on RD	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-RD-WT	B-595	Vinyl	WT on RD	0.750 (19.1)	25 ft. (7.6 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-RD-WT	B-595	Vinyl	WT on RD	1.000 (25.4)	25 ft. (7.6 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-GN-WT	B-595	Vinyl	WT on GN	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-GN-WT	B-595	Vinyl	WT on GN	0.750 (19.1)	25 ft. (7.6 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-GN-WT	B-595	Vinyl	WT on GN	1.000 (25.4)	25 ft. (7.6 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-WT-RD	B-595	Vinyl	RD on WT	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-WT-RD	B-595	Vinyl	RD on WT	0.750 (19.1)	25 ft. (7.6 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-WT-RD	B-595	Vinyl	RD on WT	1.000 (25.4)	25 ft. (7.6 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-BK-WT	B-595	Vinyl	WT on BK	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-BK-WT	B-595	Vinyl	WT on BK	0.750 (19.1)	25 ft. (7.6 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-BK-WT	B-595	Vinyl	WT on BK	1.000 (25.4)	25 ft. (7.6 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-CL-BK	B-595	Vinyl	BK on CL	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-750-595-CL-BK	B-595	Vinyl	BK on CL	0.750 (19.1)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-CL-BK	B-595	Vinyl	BK on CL	1.000 (25.4)	20 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-CL-WT	B-595	Vinyl	WT on CL	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-CL-WT	B-595	Vinyl	WT on CL	0.750 (19.1)	25 ft. (7.6 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-CL-WT	B-595	Vinyl	WT on CL	1.000 (25.4)	20 ft. (7.6 m)	1 roll (cont.)	R4400

* Average expected outdoor life of product will depend on user definition of failure, climatic conditions, mounting techniques and material colour. The 8 to 10 year outdoor durability applies to the vinyl label stock only; ribbon durability will vary.