

ASI MA PB PL AB

This item is no longer available. Should you have any questions, please contact our Sales Team.

Order No.: 2741723

The illustration shows version ASI MA PB AB



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2741723>

AS-i Gateway for PROFIBUS-DP, 62 A/B slaves, IP65 protection, incl. EMS lower part



Commercial data	
EAN	4017918915285
Pack	1 pcs.
Customs tariff	85389091
Catalog page information	Page 297 (AX-2005)

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
Interfaces	
Interface	AS-Interface
Type of connection	Flat-ribbon cable penetration technique
Power supply	
Typical current consumption	200 mA (from the AS-i network)
Electrical isolation	
Test section	Electrical isolation AS-i / INTERBUS 500 V AC
Operating elements	
Keys	2 buttons (Mode/Set) for configuring the AS-i network
Number of AS-i slaves	62

Local diagnostics	Addresses, error messages 2-character display
	Operating voltage, electronics module (UL) LED green
	Operating voltage AS-i (U ASI) LED green
	Automatic address programming active LED green
	Project planning mode active (PRJ Enable) Yellow LED
	AS-i configure error (CONFIG ERR) LED red
	AS-i transmission AS-i transmission LED green

General data

Ambient temperature (operation)	0 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Degree of protection	IP20
Weight	355 g
Width	91 mm
Height	70 mm
Length	80 mm

Accessories

Item	Designation	Description
------	-------------	-------------

Literature

2741419	ASI DOC MA PB UM	User Manual, German, for AS-i gateways for PROFIBUS-DP
2741422	ASI DOC MA PB UM E	User Manual, English, for AS-i gateways for PROFIBUS-DP

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2009 Phoenix Contact
Technical modifications reserved;