

[Products & Services](#) [Brands](#) [Technologies](#) [Our Company](#) [Partners & Suppliers](#)Search **United States** [\[Change\]](#)

## Electrical Commercial and Industrial

[Products](#) | [Documentation & Literature](#) | [News & Tradeshow](#) | [Support](#) |

[United States](#) > [Products & Services](#) > [Electronics, Electrical, and Communications](#) > [Electrical Commercial and Industrial](#) > [Products](#) > [Electrical Commercial & Industrial Products Catalog](#) > [Cable Ties and Accessories](#) > [3M™ Dual Lock Fasteners](#) > 3M™ Dual Lock™ Reclosable Fastener SJ4570 Low Profile Clear, 3/4 in x 50 yd 0.105 in (2.7 mm) , 2 per case Bulk

[Find An Account Rep](#)[Where To Buy \(Find A Distributor\)](#)[Contact Us](#)

# 3M™ Dual Lock™ Reclosable Fastener SJ4570 Low Profile Clear, 3/4 in x 50 yd 0.105 in (2.7 mm) , 2 per case Bulk

UPC# 00021200462399 3M Product Number SJ4570-3/4"x50yd-Clear 3M ID 70070967578

[Print](#)[Share](#)

A low surface energy adhesive on the back of a clear polypropylene reclosable fastener. Low profile. 0.10 inch engaged thickness. Closure life 100.

- Low profile, polyolefin fastener is half the thickness of standard Dual Lock reclosable fasteners and is self-mating.
- Designed to bond to metals, glass, many plastics and powder coated paints and medium to low surface energy materials.
- General Industrial, Specialty Vehicles, Transportation, Military, Packaging, Medical, Point of Purchase Displays, Exhibits, Electronics, Construction, Furniture, Maintenance Repair and Operations (MRO).
- Speaker Grill Attachment, Screen Door Attachment, Muntin Bars, Access Panels, Signs, Display Components, and Multi-Media Packaging.

### Need Help?

**Questions?** We can help  
[Contact Us](#)

[View All Images](#)☒ **Network Access Message: The page**

### Overview

### Support

#### Specifications

|                                            |                                                                                                                                  |
|--------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Adhesive Type                              | Low Surface Energy Acrylic Adhesive                                                                                              |
| Applications                               | Attaching Graphics                                                                                                               |
| Brand                                      | Dual Lock                                                                                                                        |
| Closure Life                               | 100                                                                                                                              |
| Color                                      | Clear                                                                                                                            |
| Engaged Thickness                          | 0.098 Inch                                                                                                                       |
| Flame Retardant                            | No                                                                                                                               |
| Indoor / Outdoor                           | Indoor                                                                                                                           |
| Industry - Use                             | Construction, Electronics, Furniture, General Industrial, Medical, Military & Government, MRO, Packaging, Retail, Transportation |
| Length                                     | 50 Linear Yard                                                                                                                   |
| Length (metric)                            | 45.72 Linear Metre                                                                                                               |
| Liner Thickness                            | 6.2 Milli-inch (mil)                                                                                                             |
| Liner Type                                 | 83# Polycoated Kraft Paper (PCK)                                                                                                 |
| Low Profile                                | Yes                                                                                                                              |
| Maximum Operating Temperature (Fahrenheit) | 158 Degree Fahrenheit                                                                                                            |
| Product Form                               | Roll                                                                                                                             |
| Units per Case                             | 2                                                                                                                                |
| Width                                      | 0.75 Inch                                                                                                                        |

|                |                  |
|----------------|------------------|
| Width (metric) | 19.05 Millimetre |
|----------------|------------------|

**3M:** [News](#) | [Careers](#) | [Investor Relations](#) | [MSDS Search](#) | [Transport Information Search](#) | [A-Z Product Index](#) | [Contact 3M](#)

[Legal Information](#) | [Privacy Policy](#)

© 3M 2012. All Rights Reserved.

