



Abrasives & Sandpaper

[Products](#) | [Solutions](#) | [Sample Request Form](#)

[Where To Buy](#) [Contact Us](#)

[Singapore](#) > [Products & Services](#) > [Abrasives & Sandpaper](#) > [Products](#) > Product Catalog

[3M™ Electrical Products](#) > [3M™ Electrical Tape](#) > [3M™ Special Use Tapes](#) > [Scotch® 48 Thread Sealant and Lubricant](#) >

Abrasives & Sandpaper

Products

- Coated and Bonded
- Surface Conditioning Abrasives
- Superabrasives
- Power Tools and Accessories

Solutions

- Deburring
- Grinding and Stock Removal
- Refining
- Microfinishing

Resources

- MSDS
- Related Links

Customer Service

- Contact Us
- Sample Request Form
- Where To Buy



[\[click to enlarge\]](#)

Scotch® Thread Sealant and Lubricant 48, 1/4" x 260" in box

Scotch® Thread Sealant and Lubricant 48 is a white unfused plastic film made of polytetrafluoroethylene (PTFE). This fluorocarbon resin film tape designed to provide a leak-resistance seal when used as a pipe thread sealant. 1/4" x 260" in box

Use Scotch® Thread Sealant and Lubricant Tape 48 to form a leak proof seal and help prevent cross threading on pipe threads.

Products

Documentation

Product / 3M Id / UPC

Scotch® Thread Sealant and Lubricant 48, 1/4" x 260" in box

3M Id : 80 - 0120 - 4710 - 8

GTIN(UPC/EAN) : 0 00 54007 06192 2

Adhesive Material	None
Backing Material	PTFE Film
Brand	Scotch
Color	White
Length	260 Inch
Maximum Operating Temperature (Celsius)	260 Degree Celsius
Operating Temperature Range	-268 to 260 Degree Celsius
Operating Temperature Range (Fahrenheit)	-450 to 500 Degree Fahrenheit
Product Family	Scotch® Thread Sealant and Lubricant 48
Product Type	PTFE Fluorocarbon Tape
RoHS 2011/65/EU Compliant	Yes
Tape Color	White
Tape Grade	Premium
Tape Length (metric)	6.6 Linear Meter
Tape Total Thickness	3 Milli-inch
Tape Total Thickness (metric)	0.076 mm
Tape Type	Special Use
Tape Width	0.25 in
Tensile Strength lb/in (N/100 mm)	5.9 (103)
Thickness	3 Milli-inch (mil)
Width	1/4 Inch