


Coaxial Cable Connector 24_MCX-50-1-13/111_N

Description

Straight bulkhead cable feed through

Interface standards
IEC 60169-36_CECC 22220



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 6 GHz

Mechanical Data

Centre contact crimped
Outer contact crimped
Weight 0.0018 kg

Environmental Data

Operating temperature -55 °C to 155 °C
2011/65/EU (RoHS - including
2015/863 and 2017/2102) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (Nickel underplated)
Body	Brass	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	
Fastening nut	Brass	Gold Plating (Nickel underplated)
Washer	Bronze	Gold Plating (Nickel underplated)
Crimp ferrule	Copper	Gold Plating (without Nickel underplating)

Related Documents

Outline drawing DOU-00008913
Catalogue drawing DCA-00008915
Assembly instruction DOC-0000182201
Mounting hole DOU-00008855

Ordering Information

Bulk 100 pcs package 24_MCX-50-1-13/111_NH

Additional Information

Suitable cables RG_178_B/U, ENVIROFLEX_178, RG_196_A/U