

Search This Product Catalog

By Keyword

- Automotive, Marine, & Aerospace
 - Product Catalog for Automotive, Marine, & Aerospace
 - 3M™ Aerospace Products and Systems
 - 3M™ Automotive Aftermarket Products and Services
 - 3M™ Automotive OEM Products
 - 3M™ Marine Products and Systems

Product Catalog for Automotive, Marine, & Aerospace > 3M™ Aerospace Products and Systems > 3M™ Tapes > 3M™ Speciality Tapes > 3M™ Polyimide Film Tape 5413 >

3M™ Polyimide Film Tape 5413 Amber, 1 in x 36 yd 2.7 mil, 9 per case Boxed

 [Printer-friendly format](#)

The 3M™ Polyimide Film Tape 5413 consist of a polyimide film and silicone adhesive. It is designed for high temperature applications. Temperature use range is -100° to 500°F (-73°C to 260°C)

3M Id : 70-0160-3922-7
GTIN(UPC/EAN) : 0 00 21200 16174 2

Additional Information

3M™ Polyimide Film Tape 5413, used as mask for protection of gold fingers of printed circuit boards during wave solder or solder dip process, release surface in fabrication of parts cured at elevated temperatures

Learn More . . .

[Packaging Data](#)

Characteristics

Adhesive Material	Silicone
Adhesive Type	Silicone Adhesive
Backing Material	Polyimide film
Length	36 Linear Yard
Magnetic Holder	Polymide Film
Size	1 in. x 36 yd. (2.5 cm x 33 m)
Tape Length	36 yd. (33 m)
Tape Type	Polymide Film
Tape Width	1 in (2.5 cm)
Temperature Range	-100F - 500F (-73C - 260C)
Thickness	2.7 Milli-inch (mil)
Width	1 Inch